

MATERIAL SAFETY DATA SHEET

SECTION 1 - PRODUCT AND COMPANY INFORMATION

Refinish Products
19699 Progress Drive
Strongsville, OH 44149

EMERGENCY PHONE NUMBERS (412) 434-4515 (U.S.)
(24 hours/day):

(514) 645-1320 (Canada)
01-800-00-21-400 (Mexico)
0632-83889090 (China)

TECHNICAL INFORMATION: (740) 363-9810 (DELAWARE, OH) 8:00 a.m. - 5:00 p.m. EST
PRODUCT SAFETY/MSDS INFORMATION: (412) 492-5555 7:00 a.m. - 4:30 p.m. EST
Product ID: T496 (0808)
PRODUCT NAME: COAGULANT
SYNONYMS: None
ISSUE DATE: 05/14/2007
EDITION NO.: 5
CHEMICAL FAMILY: TALC MIXTURE

EMERGENCY OVERVIEW:

CAUSES IRREVERSIBLE EYE DAMAGE. MAY CAUSE MODERATE SKIN IRRITATION. VAPOR AND/OR SPRAY MIST MAY BE HARMFUL IF INHALED. MAY BE HARMFUL IF SWALLOWED. This product is not expected to present any unusual hazards under fire or spill conditions. Read entire MSDS before use.

SECTION 2 - COMPOSITION INFORMATION

The following ingredient(s) marked with an "x" are considered hazardous under applicable U.S. OSHA and/or Canadian WHMIS regulations. If no ingredients are listed, then there are no U.S. OSHA and/or Canadian WHMIS hazardous ingredients in this product.

Table with 3 columns: Material/CAS Number, Percent, Hazardous. Rows include ALUMINUM SULFATE, CARBON BLACK, and CALCIUM HYDROXIDE.

SECTION 3 - HAZARDS IDENTIFICATION

ACUTE OVEREXPOSURE EFFECTS

EYE CONTACT: This product contains a material which causes irreversible eye damage. Redness, itching, burning sensation and visual disturbances may indicate excessive eye contact.
SKIN CONTACT: May cause moderate skin irritation. Dryness, itching, cracking, burning, redness, and swelling are conditions associated with excessive skin contact.
SKIN ABSORPTION: Skin absorption not expected to occur.
INHALATION: Vapor and/or spray mist may be harmful if inhaled.
INGESTION: May be harmful if swallowed.
SIGNS & SYMPTOMS OF OVEREXPOSURE: Dryness, itching, cracking, burning, redness, and swelling are conditions associated with excessive skin contact.
MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Not applicable.

CHRONIC OVEREXPOSURE EFFECTS

Avoid long-term and repeated contact. The effects of long-term, low level exposures to this product have not been determined. Safe handling of this material on a long-term basis should emphasize the prevention of all contact with this material to avoid any effects from repetitive acute exposures. See Section 11, of this MSDS for a detailed list of chronic health effects information available on individual ingredients in this product.

SECTION 4 - FIRST AID MEASURES

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Material Safety Data Sheet information available.
EYE CONTACT: Remove contact lens and pour a gentle stream of warm water through the affected eye for at least 15 minutes. Contact a poison control center, emergency room or physician right away as further treatment will be necessary.
SKIN CONTACT: Run a gentle stream of water over the affected area for 15 minutes. A mild soap may be used if available. If any symptoms persist, contact a poison control center, emergency room, or physician as further treatment may be necessary.
INHALATION: Remove from area to fresh air. If symptomatic, contact a poison control center, emergency room or physician for treatment information.
INGESTION: Gently wipe or rinse the inside of the mouth with water. Sips of water may be given if person is fully conscious. Never give anything by mouth to an unconscious or convulsing person. Do Not induce vomiting. Contact a poison control center, emergency room or physician right away as further treatment will be necessary.

SECTION 5 - FIRE FIGHTING MEASURES

FLAMMABLE PROPERTIES
FLASHPOINT: 200 Degrees F ( 93 Degrees C)
FLASHPOINT TEST METHOD: Pensky-Martens Closed Cup
UEL: Not Available.
LEL: Not Available.
AUTOIGNITION TEMPERATURE: Not Available.
EXTINGUISHING MEDIA: Use National Fire Protection Association (NFPA) Class B extinguishers (carbon dioxide, dry chemical or universal aqueous film forming foam) designed to extinguish NFPA Class IIIB combustible liquid fires.
PROTECTION OF FIREFIGHTERS: Water spray may be ineffective. Water spray may be used to cool closed containers that are exposed to extreme heat. If water is used, fog nozzles are preferable. Firefighters should wear self-contained breathing apparatus and full protective clothing.
UNUSUAL FIRE AND EXPLOSION HAZARDS: Material not known to be explosive. May produce hazardous decomposition products when exposed to extreme heat. Extreme heat includes, but is not limited to, flame cutting, brazing, and welding.

SECTION 6 - ACCIDENTAL RELEASE MEASURE

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Provide maximum ventilation. Only personnel equipped with proper respiratory, skin, and eye protection should be permitted in the area. Remove all sources of ignition. Take up spilled material with sand, vermiculite, or other noncombustible absorbent material and place in clean, empty containers for disposal. Only the spilled material and the absorbant should be placed in this container.

**SECTION 7 - HANDLING AND STORAGE**

**PRECAUTIONS TO BE TAKEN DURING HANDLING AND STORAGE:**

If this material is part of a multiple component system, read the Material Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.

**STORAGE:**

Do not store above 120 degrees F.(48 degrees C.). Store large quantities in buildings designed and protected for storage of NFPA Class IIIB combustible liquids.

**SECTION 8 - EXPOSURE CONTROLS & PERSONAL PROTECTION**

**ENGINEERING CONTROLS:**

Provide general dilution or local exhaust ventilation in volume and pattern to keep the concentration of ingredients listed in Section 8 below the lowest suggested exposure limits, the LEL below the stated limit, and to remove decomposition products during welding or flame cutting.

**PERSONAL PROTECTIVE EQUIPMENT**

**EYES:**

Wear chemical-type splash goggles and full face shield when possibility exists for eye contact due to splashing or spraying liquid, airborne particles, or vapors.

**SKIN/GLOVES:**

Wear protective clothing to prevent skin contact. Apron and gloves should be constructed of: rubber. No specific permeation/degradation testing have been done on protective clothing for this product. Recommendations for skin protection are based on infrequent contact with this product. For frequent contact or total immersion, contact a manufacturer of protective clothing for appropriate chemical impervious equipment. The decision whether to clean or discard contaminated clothing should be based on the chemicals contaminating them. Some chemicals can cause skin irritation, sensitization or other health effects if the cleaning process does not remove all traces of them. Consult a safety professional to determine whether clothing contaminated with this product can be safely cleaned and reused.

**RESPIRATOR:**

Where ventilation is inadequate, use a NIOSH- approved air purifying respirator with the appropriate chemical cartridges or positive- pressure, air-supplied respirator. Read the respirator manufacturer's instructions and literature carefully to determine the type of airborne contaminants against which the respirator is effective, its limitations, and how it is to be properly fitted and used. Provide general dilution or local exhaust ventilation in volume and pattern to keep the concentration of ingredients listed in Section 2 below the lowest suggested exposure limits, the LEL below the stated limit, and to remove decomposition products during welding or flame cutting.

**GENERAL HYGIENE - ESTABLISHED EXPOSURE LIMITS**

If Threshold Limit Values (TLVs) have been established by ACGIH, OSHA, Ontario or PPG, they will be listed below. These limits are intended for use in the practice of industrial hygiene as guidelines or recommendations in the control of potential workplace health hazards. These limits are not a relative index of toxicity and should not be used by anyone without industrial hygiene training.

| Material/<br>CAS Number           | Percent | ACGIH TLV             | ACGIH<br>STEL      | OSHA PEL              | OSHA<br>STEL       |
|-----------------------------------|---------|-----------------------|--------------------|-----------------------|--------------------|
| CARBON BLACK<br>1333-86-4         | 10 - 30 | 3.5 mg/m <sup>3</sup> | Not<br>established | 3.5 mg/m <sup>3</sup> | Not<br>established |
| CALCIUM<br>HYDROXIDE<br>1305-62-0 | 5 - 10  | 5 mg/m <sup>3</sup>   | Not<br>established | 5 mg/m <sup>3</sup>   | Not<br>established |

| Material/<br>CAS Number           | Percent | Ontario<br>TWA        | Ontario<br>STEL    | PPG IPEL           | PPG STEL           |
|-----------------------------------|---------|-----------------------|--------------------|--------------------|--------------------|
| CARBON BLACK<br>1333-86-4         | 10 - 30 | 3.5 mg/m <sup>3</sup> | Not<br>established | Not<br>established | Not<br>established |
| CALCIUM<br>HYDROXIDE<br>1305-62-0 | 5 - 10  | 5 mg/m <sup>3</sup>   | Not<br>established | Not<br>established | Not<br>established |

**Key:** ACGIH=American Conference of Governmental Industrial Hygienists; OSHA=Occupational Safety and Health Administration; TLV=Threshold Limit Value; TWA=Time Weighted Average; PEL=Permissible Exposure Limit (1989 Vacated values); IPEL=Internal Permissible Exposure Limit; Ceiling=TLV or PEL Ceiling Limit; STEL=TLV or PEL Short-Term Exposure Limit; Skin= Skin Absorption Designation. [C- Ceiling Limit; S-Potential Skin Absorption; R-Respirable Dust] **Additional Information Not applicable.**

**SECTION 9 - PHYSICAL & CHEMICAL PROPERTIES**

**(FORMULA VALUES, NOT SALES SPECIFICATIONS)**

**SPECIFIC GRAVITY:** 1.224  
**PHYSICAL STATE:** Liquid  
**Percent Solids:** 100.00  
**Percent Volatile by Volume:** .000  
**pH:** Not available.  
**ODOR THRESHOLD:** Not available.  
**Vapour Pressure:** N.A. mmHg  
**ODOR/APPEARANCE:** Viscous liquid with an odor characteristic of the solvents listed in Section 2.  
**VAPOR DENSITY:** HEAVIER THAN AIR  
**Evaporation Rate:** 0  
**BOILING POINT OR RANGE:** Not available.  
**Freezing Point or Range:** Not Applicable.  
**Melting Point or Range(°C):** Not Applicable.  
**Partition coefficient (n-octanol/water):** Not Applicable.  
**WEIGHT PER GALLON:** 10.20 (U.S.) / 12.2 (IMPERIAL)

**SECTION 10 - STABILITY AND REACTIVITY**

**STABILITY:**  
This product is normally stable and will not undergo hazardous reactions.  
**CONDITIONS TO AVOID:**  
None Known.  
**INCOMPATIBLE MATERIALS:**  
Avoid contact with strong alkalis, strong mineral acids, or strong oxidizing agents.  
**HAZARDOUS POLYMERIZATION:**  
None Known.  
**HAZARDOUS DECOMPOSITION PRODUCTS:**  
- Carbon monoxide - Carbon dioxide

**SECTION 11 - TOXICOLOGICAL INFORMATION**

**ACUTE TOXICITY**

**Refinish Products**  
**19699 Progress Drive**  
**Strongsville, OH 44149**

Product ID: T496 (0808)  
**PRODUCT NAME: COAGULANT**

| Material/<br>CAS Number           | Percent | ORAL<br>LD50 (g/kg) | DERMAL<br>LD50 (g/kg) | INHALATION<br>LC50 (mg/l) |
|-----------------------------------|---------|---------------------|-----------------------|---------------------------|
| ALUMINUM<br>SULFATE<br>10043-01-3 | 10 - 30 | 6.21 g/kg           | Not Available         | Not Available             |
| CARBON BLACK<br>1333-86-4         | 10 - 30 | 15.40 g/kg          | 3.00 g/kg             | Not Available             |
| CALCIUM<br>HYDROXIDE<br>1305-62-0 | 5 - 10  | 7.34 g/kg           | Not Available         | Not Available             |

**CHRONIC TOXICITY**

**Ingredient Target Organ/Chronic Effects:**  
 - Carcinogen

**Mutagenicity Toxicity:**

This has not been tested for this product.

**Reproductive Toxicity:**

This has not been tested for this product.

**SUPPLEMENTAL HEALTH INFORMATION:**

| Material/<br>CAS<br>Number   | Percent | Ingredient Specific Animal Data:  |
|------------------------------|---------|---|
| CARBON<br>BLACK<br>1333-86-4 | 10 - 30 | This product contains carbon black which has been rated an IARC 2B carcinogen due to animal data. |

**SECTION 12 - ECOLOGICAL INFORMATION**

**POTENTIAL ENVIRONMENTAL EFFECTS**

**Ecotoxicity:** No Information Available.

**ENVIRONMENTAL FATE**

**Mobility:** No information available.  
**Biodegradation:** No information available.  
**Bioaccumulation:** No Information Available.

**PHYSICAL/CHEMICAL**

**Hydrolysis:** No information available.  
**Photolysis:** No information available.

**SECTION 13 - DISPOSAL CONSIDERATIONS**

Provide maximum ventilation, only personnel equipped with proper respiratory and skin and eye protection should be permitted in the area. Take up spilled material with sawdust, vermiculite, or other absorbent material and place in containers for disposal. Waste material must be disposed of in accordance with federal, state, provincial and local environmental control regulations. Empty containers should be recycled by an appropriately licensed reconditioner/salvager or disposed of through a permitted waste management facility. Additional disposal information is contained on the Environmental Data Sheet for this product, which can be obtained from your PPG representative.

**SECTION 14 - TRANSPORTATION INFORMATION**

**Proper Shipping Name:** Paint Related Material- Non-Regulated Goods  
**NOS Technical Name:** None  
**Hazard Class:** None  
**Subsidiary Class(es):** None  
**UN Number:** None  
**Packing Group:** None

**USA - RQ Hazardous Substances:** None

**USA-RQ Hazardous Substance** None  
**Threshold Ship Weight:**  
**Marine Pollutant Name:** None

**SECTION 15 - REGULATORY INFORMATION**

**INVENTORY STATUS**

**U.S. TSCA:** This product and/or all of its components are listed on the U.S. TSCA Inventory or is otherwise exempt from TSCA Inventory reporting requirements.

**FEDERAL REGULATIONS**

**US Regulations**

| Material/<br>CAS Number           | Percent | CERCLA HS -<br>RQ (LBS) | SARA EHS-<br>TPQ (LBS) | SARA 313   |
|-----------------------------------|---------|-------------------------|------------------------|------------|
| ALUMINUM<br>SULFATE<br>10043-01-3 | 10 - 30 | 5000 lbs                | Not Listed             | Not Listed |
| CARBON BLACK<br>1333-86-4         | 10 - 30 | Not Listed              | Not Listed             | Not Listed |
| CALCIUM<br>HYDROXIDE<br>1305-62-0 | 5 - 10  | Not Listed              | Not Listed             | Not Listed |

**SARA 311/312**

**Health (acute):** Yes  
**Health (chronic):** Yes  
**Fire (flammable):** No  
**Pressure:** No  
**Reactivity:** No

**WHMIS HAZARD CLASS:** - Class D, Division 2, Subdivision A - Class D, Division 2, Subdivision B

**STATE/PROVINCIAL REGULATIONS**

**CALIFORNIA PROP. 65:** WARNING: This product contains a chemical known to the State of California to cause cancer.

**Additional Information**

| Material/<br>CAS Number   | Percent | IARC<br>Group<br>1(Kno<br>wn<br>Human<br>Carc.) | IARC<br>Group<br>2A<br>(Proba<br>ble<br>Carc.) | IARC<br>2B (Suspec<br>ted<br>Carc.) | ACGIH<br>Carc. | NTP<br>Known<br>Carc. | OSHA<br>Carc. |
|---------------------------|---------|---|--|-------------------------------------|----------------|-----------------------|---------------|
| CARBON BLACK<br>1333-86-4 | 10 - 30 | N   | N  | Y                                   | N              | N                     | Y             |

**Key:** IARC- International Agency on the Research of Cancer; ACGIH- American Conference of Governmental Industrial Hygienists; NTP- National Toxicology Program \*Denotes chemical as NTP Known Carcinogen; + Denotes NTP Possible Carcinogen; OSHA- Occupational Safety and Health Administration.

**SECTION 16 - OTHER INFORMATION**

**Hazard Rating Systems**

**NFPA Rating:** 3 10  
**HMIS Rating:** 3\*10

**Rating System:** 0=Minimal, 1=Slight, 2=Moderate, 3=Serious, 4=Severe, \*=Chronic Effects.

HMIS=Hazardous Materials Identification System; NFPA=National Fire Protection Association;

Safe handling of this product requires that all of the information on the MSDS be evaluated for specific work environments and conditions of use.

---

**Refinish Products  
19699 Progress Drive  
Strongsville, OH 44149**

**Product ID: T496 (0808)  
PRODUCT NAME: COAGULANT**

**PREPARED BY:** Product Safety Department  
**REASON FOR REVISION:** Date. Edition.  
Updated MSDS  
format.

This Material Safety Data Sheet has been prepared in accordance with Canada's Workplace Hazardous Materials Information System (WHMIS) and the OSHA Hazard Communication Standard (29 CFR 1910.1200), the supplier notification requirements of SARA Title III, Section 313 and other applicable right-to-know regulations.

Additional environmental information is contained on the Environmental Data Sheet for this product, which can be obtained from your PPG representative.

T496 000001 (00461829.001)(05/11/07)  
070510, 000, 0808

\*\*\* END OF MSDS \*\*\*