

MATERIAL SAFETY DATA SHEET

SECTION 1 - PRODUCT AND COMPANY INFORMATION

PPG Industries, Inc.
One PPG Place
Pittsburgh, PA 15272

EMERGENCY PHONE NUMBERS (412) 434-4515 (U.S.)
(24 hours/day):

(514) 645-1320 (Canada)
01-800-00-21-400 (Mexico)
0532-83889090 (China)

TECHNICAL INFORMATION: (740) 363-9610 (DELAWARE, OH) 8:00 a.m. - 5:00 p.m. EST
PRODUCT SAFETY/MSDS INFORMATION: (412) 492-5555 7:00 a.m. - 4:30 p.m. EST

Product ID: P935-2019 (0808)
PRODUCT NAME: AQUABASE PLUS ACTIVATOR
SYNONYMS: None
ISSUE DATE: 09/19/2007
EDITION NO.: 3
CHEMICAL FAMILY: POLYISOCYANATE

EMERGENCY OVERVIEW:

Combustible. Keep away from heat, sparks, flames, and other sources of ignition. Do not smoke. CAUSES SEVERE EYE IRRITATION. MAY CAUSE MODERATE SKIN IRRITATION. MAY BE ABSORBED THROUGH THE SKIN. PROLONGED OR REPEATED CONTACT MAY CAUSE AN ALLERGIC SKIN REACTION. VAPOR AND/OR SPRAY MIST MAY BE HARMFUL IF INHALED. SKIN CONTACT TO ISOCYANATE MONOMER MAY LEAD TO ALLERGIC LUNG REACTION. MAY IRRITATE LUNGS. VAPOR IRRITATES EYES, NOSE, AND THROAT. VAPOR GENERATED AT ELEVATED TEMPERATURES IRRITATES EYES, NOSE AND THROAT. MAY CAUSE IRRITATION AND/OR ALLERGIC RESPIRATORY REACTION IN LUNGS. HARMFUL IF SWALLOWED. STABLE - HAZARDOUS REACTIONS POSSIBLE AT EXTREMELY HIGH TEMPERATURES/PRESSURES.

SECTION 2 - COMPOSITION INFORMATION

The following ingredient(s) marked with an "x" are considered hazardous under applicable U.S. OSHA and/or Canadian WHMIS regulations. If no ingredients are listed, then there are no U.S. OSHA and/or Canadian WHMIS hazardous ingredients in this product.

Material/ CAS Number	Percent	Hazardous	
POLYISOCYANATE Proprietary	40 - 70	X	
1-METHOXY-2-PROPYL ACETATE 108-65-6	10 - 30	X	
XYLENES 1330-20-7	10 - 30	X	
ETHYL BENZENE 100-41-4	1 - 5	X	
ISOPHORONE DIISOCYANATE 4098-71-9	0.1-1.0	X	
(As Diisocyanates) 4098-71-9	*	X	See Sections 8 and 15 for information.

SECTION 3 - HAZARDS IDENTIFICATION

ACUTE OVEREXPOSURE EFFECTS

EYE CONTACT:
Causes severe eye irritation. Redness, itching, burning sensation and visual disturbances may indicate excessive eye contact.

SKIN CONTACT:

May cause moderate skin irritation. Dryness, itching, cracking, burning, redness, and swelling are conditions associated with excessive skin contact.

SKIN ABSORPTION:

May be absorbed through the skin. Prolonged or repeated contact may cause an allergic skin reaction.

INHALATION:

Vapor and/or spray mist may be harmful if inhaled. Animal tests indicate that skin contact alone to monomeric isocyanates may lead to allergic respiratory reaction. May irritate lungs. Vapor irritates eyes, nose, and throat. Vapor generated at elevated temperatures irritates eyes, nose and throat. May cause irritation and/or allergic respiratory reaction in lungs.

INGESTION:

Harmful if swallowed.

SIGNS & SYMPTOMS OF OVEREXPOSURE:

Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Eye watering, headaches, nausea, dizziness and loss of coordination are indications that solvent levels are too high. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. Dryness, itching, cracking, burning, redness, and swelling are conditions associated with excessive skin contact.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Do not use if you have chronic (long-term) lung or breathing problems, or if you have ever had a reaction to isocyanates.

CHRONIC OVEREXPOSURE EFFECTS

Avoid long-term and repeated contact. Repeated exposure to vapors above recommended exposure limits (see Section 8) may cause irritation of the respiratory system and permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. Prolonged exposure to an ingredient(s) in this product may cause kidney and/or liver damage. This product contains isocyanates. Inhalation may cause a burning sensation of the nose, throat and lungs. Allergic respiratory reactions to these materials are characterized by asthma-like symptoms such as chest tightness, wheezing, shortness of breath and coughing. These symptoms may follow repeated exposure or a single massive exposure and may be delayed. High exposures to xylenes in some animal studies have been reported to cause health effects on the developing embryo and fetus. These effects were often at levels toxic to the mother. There is some evidence that repeated exposure to organic solvent vapors in combination with constant loud noise can cause greater hearing loss than expected from exposure to noise alone. The effects of long-term, low level exposures to this product have not been determined. Safe handling of this material on a long-term basis should emphasize the prevention of all contact with this material to avoid any effects from repetitive acute exposures. See Section 11, of this MSDS for a detailed list of chronic health effects information available on individual ingredients in this product.

SECTION 4 - FIRST AID MEASURES

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Material Safety Data Sheet information available.

EYE CONTACT:

Remove contact lens and pour a gentle stream of warm water through the affected eye for at least 15 minutes. If irritation persists, contact a poison control center, emergency room, or physician as further treatment may be necessary.

SKIN CONTACT:

Run a gentle stream of water over the affected area for 15 minutes. A mild soap may be used if available. If any symptoms persist, contact a poison control center, emergency room, or physician as further treatment may be necessary.

INHALATION:

Remove from area to fresh air. If symptomatic, contact a poison control center, emergency room or physician for treatment information.

INGESTION:

Gently wipe or rinse the inside of the mouth with water. Sips of water may be given. Never give anything by mouth to an unconscious person. Contact a poison control center, emergency room or physician right away as further treatment may be necessary.

SECTION 5 - FIRE FIGHTING MEASURES

FLAMMABLE PROPERTIES

FLASHPOINT: 104 Degrees F (40 Degrees C)

FLASHPOINT TEST METHOD:

Pensky-Martens Closed Cup

UEL: Not Available.

LEL: 1.2

AUTOIGNITION TEMPERATURE:

Not Available.

EXTINGUISHING MEDIA:

Use National Fire Protection Association (NFPA) Class B extinguishers (carbon dioxide, dry chemical, or universal aqueous film forming foam) designed to extinguish NFPA Class II combustible liquid fires. Water spray may be ineffective. Water spray may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

PROTECTION OF FIREFIGHTERS:

Fire-fighters should wear self-contained breathing apparatus and full protective clothing.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Keep this product away from heat, sparks, flame, and other sources of ignition (i.e., pilot lights, electric motors, static electricity). Invisible vapors can travel to a source of ignition and flash back. Do not smoke while using this product. Keep containers tightly closed when not in use. Closed containers may explode when overheated. Do not apply to hot surfaces. Toxic gases may form when this product comes in contact with extreme heat. May produce hazardous decomposition products when exposed to extreme heat. Extreme heat includes, but is not limited to, flame cutting, brazing, and welding.

SECTION 6 - ACCIDENTAL RELEASE MEASURE

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

Provide maximum ventilation. Only personnel equipped with proper respiratory, skin, and eye protection should be permitted in the area. Remove all sources of ignition. Take up spilled material with sand, vermiculite, or other noncombustible absorbent material and place in clean, empty containers for disposal. Only the spilled material and the absorbant should be placed in this container.

SECTION 7 - HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN DURING HANDLING AND STORAGE:

Vapors may collect in low areas. If this material is part of a multiple component system, read the Material Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts. Containers should be grounded when pouring. Avoid free fall of liquids in excess of a few inches.

STORAGE:

Do not store above 120 degrees F.(48 degrees C.). Store large quantities in buildings designed and protected for storage of NFPA Class II combustible liquids.

SECTION 8 - EXPOSURE CONTROLS & PERSONAL PROTECTION

ENGINEERING CONTROLS:

Provide general dilution or local exhaust ventilation in volume and pattern to keep the concentration of ingredients listed in Section 8 below the lowest suggested exposure limits, the LEL below the stated limit, and to remove decomposition products during welding or flame cutting.

PERSONAL PROTECTIVE EQUIPMENT

EYES:

Wear chemical-type splash goggles when possibility exists for eye contact due to splashing or spraying liquid, airborne particles, or vapors.

SKIN/GLOVES:

Wear protective clothing to prevent skin contact. Apron and gloves should be constructed of: impermeable material. No specific permeation/degradation testing have been done on protective clothing for this product. Recommendations for skin protection are based on infrequent contact with this product. For frequent contact or total immersion, contact a manufacturer of protective clothing for appropriate chemical impervious equipment. The decision whether to clean or discard contaminated clothing should be based on the chemicals contaminating them. Some chemicals can cause skin irritation, sensitization or other health effects if the cleaning process does not remove all traces of them. Consult a safety professional to determine whether clothing contaminated with this product can be safely cleaned and reused.

RESPIRATOR:

Where vapors or overspray are present, use a NIOSH approved, positive-pressure, air- supplied respirator for the entire time of spraying and until all vapors and mists are gone. Follow the respirator manufacturer's directions for respirator use. Provide general dilution or local exhaust ventilation in volume and pattern to keep the concentration of ingredients listed in Section 2 below the lowest suggested exposure limits, the LEL below the stated limit, and to remove decomposition products during welding or flame cutting.

GENERAL HYGIENE - ESTABLISHED EXPOSURE LIMITS

If Threshold Limit Values (TLVs) have been established by ACGIH, OSHA, Ontario or PPG, they will be listed below. These limits are intended for use in the practice of industrial hygiene as guidelines or recommendations in the control of potential workplace health hazards. These limits are not a relative index of toxicity and should not be used by anyone without industrial hygiene training.

Material/ CAS Number	Percent	ACGIH TLV	ACGIH STEL	OSHA PEL	OSHA STEL
XYLENES 1330-20-7	10 - 30	100 ppm	150 PPM	100 ppm	150 ppm
ETHYL BENZENE 100-41-4	1 - 5	100 ppm	125 ppm	100 ppm	125 ppm
ISOPHORONE DIISOCYANATE 4098-71-9	0.1-1.0	0.005 PPM	Not established	S- 0.005 ppm	0.02 ppm

Material/ CAS Number	Percent	Ontario TWA	Ontario STEL	PPG IPEL	PPG STEL
1-METHOXY-2- PROPYL ACETATE 108-65-6	10 - 30	50 PPM	Not established	50 PPM	Not established
XYLENES 1330-20-7	10 - 30	100 ppm	150 ppm	Not established	Not established
ETHYL BENZENE 100-41-4	1 - 5	100 PPM	125 PPM	Not established	Not established
ISOPHORONE DIISOCYANATE 4098-71-9	0.1-1.0	C- 0.02 ppm	Not established	Not established	Not established

Key: ACGIH=American Conference of Governmental Industrial Hygienists; OSHA=Occupational Safety and Health Administration; TLV=Threshold Limit Value; TWA=Time Weighted Average; PEL=Permissible Exposure Limit (1989 Vacated values); IPEL=Internal Permissible Exposure Limit; Ceiling=TLV or PEL Ceiling Limit; STEL=TLV or PEL Short-Term Exposure Limit; Skin= Skin Absorption Designation. [C- Ceiling Limit; S-Potential Skin Absorption; R-Respirable Dust] **Additional Information** Not applicable.

SECTION 9 - PHYSICAL & CHEMICAL PROPERTIES

(FORMULA VALUES, NOT SALES SPECIFICATIONS)

SPECIFIC GRAVITY: 1.070
PHYSICAL STATE: Liquid
Percent Solids: 70.00
Percent Volatile by Volume: 35.200
pH: Not available.
ODOR THRESHOLD: Not available.
Vapour Pressure: 4.4 mmHg
ODOR/APPEARANCE: Viscous liquid with an odor characteristic of the solvents listed in Section 2.

VAPOR DENSITY: HEAVIER THAN AIR
Evaporation Rate: 51
BOILING POINT OR RANGE: 280 - 302Degrees F
Freezing Point or Range: Not Applicable.
Melting Point or Range(°C): Not Applicable.
Partition coefficient (n-octanol/water): Not Applicable.
WEIGHT PER GALLON: 8.92 (U.S.) / 10.7 (IMPERIAL)

SECTION 10 - STABILITY AND REACTIVITY

STABILITY:
This product is normally stable but may undergo hazardous reactions at extremely high temperatures and pressures.

CONDITIONS TO AVOID:

None Known.

INCOMPATIBLE MATERIALS:

Avoid contact with strong alkalis, strong mineral acids, or strong oxidizing agents. Avoid water and alcohols.

HAZARDOUS POLYMERIZATION:

None Known.

HAZARDOUS DECOMPOSITION PRODUCTS:

- Carbon monoxide - Carbon dioxide - Traces of isocyanate - Oxides of nitrogen - Hydrogen cyanide

SECTION 11 - TOXICOLOGICAL INFORMATION

ACUTE TOXICITY

Material/ CAS Number	Percent	ORAL LD50 (g/kg)	DERMAL LD50 (g/kg)	INHALATION LC50 (mg/l)
POLYISOCYANATE Proprietary	40 - 70	4.30 g/kg	1.70 g/kg	Not Available
1-METHOXY-2- PROPYL ACETATE 108-65-6	10 - 30	8.53 g/kg	5.00 g/kg	Not Available
XYLENES 1330-20-7	10 - 30	4.30 g/kg	1.70 g/kg	21.88 mg/l 4 hr
ETHYL BENZENE 100-41-4	1 - 5	3.50 g/kg	17.80 g/kg	Not Available
ISOPHORONE DIISOCYANATE 4098-71-9	0.1-1.0	Not Available	1.10 g/kg	Not Available

CHRONIC TOXICITY

Ingredient Target Organ/Chronic Effects:

- Respiratory sensitizer - Carcinogen - Embryotoxin - Brain - Central nervous system - Lung - Ear - Kidney - Liver

Mutagenicity Toxicity:

This has not been tested for this product.

Reproductive Toxicity:

This has not been tested for this product.

SUPPLEMENTAL HEALTH INFORMATION:

Material/ CAS Number	Percent	Ingredient Specific Animal Data:
ETHYL BENZENE 100-41-4	1 - 5	Ethylbenzene has been reported by NTP to cause cancer in laboratory animals following a chronic (2 year) inhalation exposure. Dose levels of 75, 250 and 750 ppm were used, with evidence of carcinogenicity found in the kidneys of rats and the lung and liver of mice at 750 ppm. The No Observed Effect Level (NOEL) was 75 ppm. The relevance of these findings to humans is uncertain, but appropriate safeguards should be employed to reduce or eliminate inhalation exposure to ethylbenzene.

SECTION 12 - ECOLOGICAL INFORMATION

POTENTIAL ENVIRONMENTAL EFFECTS

Ecotoxicity: No Information Available.

ENVIRONMENTAL FATE

Mobility: No information available.

Biodegradation: No information available.

Bioaccumulation: No Information Available.

PHYSICAL/CHEMICAL

Hydrolysis: No information available.

Photolysis: No information available.

SECTION 13 - DISPOSAL CONSIDERATIONS

Provide maximum ventilation, only personnel equipped with proper respiratory and skin and eye protection should be permitted in the area. Take up spilled material with sawdust, vermiculite, or other absorbent material and place in containers for disposal.

Waste material must be disposed of in accordance with federal, state, provincial and local environmental control regulations. Empty containers should be recycled by an appropriately licensed reconditioner/salvager or disposed of through a permitted waste management facility. Additional disposal information is contained on the Environmental Data Sheet for this product, which can be obtained from your PPG representative.

SECTION 14 - TRANSPORTATION INFORMATION

Proper Shipping Name: Paint
NOS Technical Name: None
Hazard Class: 3
Subsidiary Class(es): None
UN Number: UN1263
Packing Group: III

USA - RQ Hazardous Substances: Xylenes, Ethyl Benzene

USA-RQ Hazardous Substance Xylenes>666.6 Pounds, Ethyl

Threshold Ship Weight: Benzene>33333.67 Pounds

Marine Pollutant Name: None

USA and Canada Shipments Only- Combustible Liquid Exception: Non-bulk (<=119 Gallons/450 L) ground shipments can be reclassified to "not regulated" for transportation. Bulk shipments - USA Only (> 119 Gallons/450 L) can be reclassified to a Combustible Liquid.

USA Shipments Only - RQ Threshold Ship Weight: This is the total weight of this product that must be shipped to exceed the RQ quantity.

SECTION 15 - REGULATORY INFORMATION

INVENTORY STATUS

U.S. TSCA: This product and/or all of its components are listed on the U.S. TSCA Inventory or is otherwise exempt from TSCA inventory reporting requirements.

FEDERAL REGULATIONS
US Regulations

Material/ CAS Number	Percent	CERCLA HS - RQ (LBS)	SARA EHS - TPQ (LBS)	SARA 313
POLYISOCYANATE Proprietary	40 - 70	Not Listed	Not Listed	Not Listed
1-METHOXY-2- PROPYL ACETATE 108-85-6	10 - 30	Not Listed	Not Listed	Not Listed
XYLENES 1330-20-7	10 - 30	100 lbs	Not Listed	Listed
ETHYL BENZENE 100-41-4	1 - 5	1000 lbs	Not Listed	Listed
ISOPHORONE DIISOCYANATE 4098-71-9	0.1-1.0	Not Listed	500 LBS	Not Listed
(As Diisocyanates) 4098-71-9	*	Not Listed	Not Listed	Listed

PREPARED BY: Product Safety Department
REASON FOR REVISION: Section 1 has been updated. Section 3 has been updated. Section 14 has been updated. Date. Edition.
Updated MSDS format.

This Material Safety Data Sheet has been prepared in accordance with Canada's Workplace Hazardous Materials Information System (WHMIS) and the OSHA Hazard Communication Standard (29 CFR 1910.1200), the supplier notification requirements of SARA Title III, Section 313 and other applicable right-to-know regulations. Additional environmental information is contained on the Environmental Data Sheet for this product, which can be obtained from your PPG representative.
P935-2019 000001 (00467801.003)(09/18/07)
070611, 000, 0808

*** END OF MSDS ***

SARA 311/312

Health (acute): Yes
Health (chronic): Yes
Fire (flammable): Yes
Pressure: No
Reactivity: No

WHMIS HAZARD CLASS: - Class B, Division 3 - Class D, Division 2, Subdivision A - Class D, Division 2, Subdivision B

STATE/PROVINCIAL REGULATIONS

CALIFORNIA PROP. 65: WARNING: This product contains a chemical known to the State of California to cause cancer.

Additional Information

Material/ CAS Number	Percent	IARC Group 1(Kno wn Human Carc.)	IARC Group 2A (Proba ble Carc.)	IARC 2B (Suspec ted Carc.)	ACGIH Carc.	NTP Known Carc.	OSHA Carc.
ETHYL BENZENE 100-41-4	1-5	N	N	Y	N	N	Y

Key: IARC- International Agency on the Research of Cancer; ACGIH- American Conference of Governmental Industrial Hygienists; NTP- National Toxicology Program *Denotes chemical as NTP Known Carcinogen; + Denotes NTP Possible Carcinogen; OSHA- Occupational Safety and Health Administration.

SECTION 16 - OTHER INFORMATION

Hazard Rating Systems

NFPA Rating: 3 21

HMIS Rating: 3*21

Rating System: 0=Minimal, 1=Slight, 2=Moderate, 3=Serious, 4=Severe, *=Chronic Effects.

HMIS=Hazardous Materials Identification System; NFPA=National Fire Protection Association;

Safe handling of this product requires that all of the information on the MSDS be evaluated for specific work environments and conditions of use.