



**GULF OIL
MATERIAL SAFETY DATA SHEET**


GULF UNIVERSAL TRACTOR FLUID

PAGE 1

Product Code: 331953

NFPA HAZARD RATING

- 4 - Extreme
- 3 - High
- 2 - Moderate
- 1 - Slight
- 0 - Insignificant



DIVISION AND LOCATION---SECTION I

Division: MASTER DISTRIBUTOR OF GULF LUBRICANTS
Location: AMERICAN REFINING GROUP INC
77 N. KENDALL AVENUE, BRADFORD, PA, 16701
Emergency Telephone Number: 814-368-1297
Transportation Emergency: CHEMTREC 1-(800) 424-9300 (U.S. and Canada)

CHEMICAL AND PHYSICAL PROPERTIES---SECTION II

Chemical Name: petroleum hydrocarbon
Formula: not applicable
Hazardous Decomposition Products:
carbon monoxide and carbon dioxide from burning.
oxides of phosphorous from burning
oxides of sulfur
Incompatibility (Keep away from):
strong oxidizers such as hydrogen peroxide, bromine, and chromic acid.
Toxic and Hazardous Ingredients: none
Form: liquid **Odor:** motor oil
Appearance: liquid **Color:** brown
Specific Gravity (water=1): .88
Boiling Point: greater than 330°C (625°F)
Melting Point: less than -26°C (-15°F)
Solubility in Water (by weight %): 0 at 20°C
Volatile (by weight %): 0
Evaporation Rate: 0
Vapor Pressure (mm Hg at 20°C): 0
Vapor Density (air=1): not volatile
pH (as is): not applicable
Stability: Product is stable under normal conditions
Viscosity SUS at 100°F: Greater than or = to 100

(Continued on next page)



**GULF OIL
MATERIAL SAFETY DATA SHEET**

GULF UNIVERSAL TRACTOR FLUID

Product Code: 331953

PAGE 2

FIRE AND EXPLOSION DATA---SECTION III

Special Fire Fighting Procedures:

Do not use water except as fog.

Unusual Fire and Explosion Hazards:

Do not cut, weld, braze, solder, drill, grind or expose containers, drums, tanks, etc. of product to heat, flame, sparks, static electricity or other sources of ignition; they may ignite explosively.

Flashpoint: (Method Used) Cleveland open cup greater than 193°C (380°F)

Flammable limits % : not applicable

Extinguishing agents:

Drychemical or Waterfog or CO2 or Foam

Closed containers exposed to fire may be cooled with water.

HEALTH HAZARD DATA---SECTION IV

Permissible concentrations (air):

see COMMENTS section

Chronic effects of overexposure:

no data available

Acute toxicological properties:

no data available

Emergency First Aid Procedures:

Eyes: Immediately flush with large quantities of water for at least 15 minutes and call a physician.

Skin Contact: Remove excess with cloth or paper. Wash thoroughly with soap and water.

Inhalation: Remove victim to fresh air. Call a physician.

If Swallowed: Contact a physician immediately.

SPECIAL PROTECTION INFORMATION---SECTION V

Ventilation Type Required (Local, mechanical, special): see COMMENTS section

Respiratory Protection (Specify type): Use NIOSH/MSHA certified respirator with dual organic vapor/mist and particulates cartridge if vapor concentration exceeds permissible exposure limit.

Protective Gloves: neoprene type

Eye Protection: chemical safety goggles

other Protective Equipment: none

(Continued on next page)



GULF OIL
MATERIAL SAFETY DATA SHEET

GULF UNIVERSAL TRACTOR FLUID

Product Code: 331953

PAGE 3

HANDLING OF SPILLS OR LEAKS--SECTION VI

Procedures for Clean-Up: Transfer bulk of mixture into another container. Absorb residue with an inert material such as earth, sand, or vermiculite. Sweep up and dispose as solid waste in accordance with local, state, and federal regulations.

Waste Disposal: Dispose of in accordance with all applicable federal, state and local regulations.

SPECIAL PRECAUTIONS---SECTION VII

Precautions to be taken in handling and storage:

Do not handle or store at temperatures over

Maximum Storage Temperature: 60 ° C (140 ° F)

TRANSPORTATION DATA---SECTION VIII

D.O.T: Not Regulated

Reportable Quantity : not applicable

Freight Classification: Petroleum Lubricating Oil

Special Transportation Notes: none

ENVIRONMENTAL/SAFETY REGULATIONS---SECTION IX

Section 313 (Title III Superfund Amendment and Reauthorization Act):

This product contains the following toxic chemical category(ies) subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372 (percent by weight is also provided): 1.6% zinc compound or .13% zinc in compound form

COMMENTS

The additive mixtures in this product have been declared a trade secret by the additive manufacturers.

If used in applications where a mist may be generated, observe a TWA/PEL of 5 mg/m³ for mineral oil mist (OSHA and ACGIH).

(Continued on next page)



**GULF OIL
MATERIAL SAFETY DATA SHEET**

GULF UNIVERSAL TRACTOR FLUID

Product Code: 331953

PAGE 4

(COMMENTS continued)

Prepared by: R. M. KELLAM
Title: PRODUCT SAFETY & HEALTH COORDINATOR
Original Date: 06/15/98 Sent to:
Revision Date: 02/14/00
Supersedes : 06/15/98
Date Sent

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind, express or implied, and we assume no responsibility for any loss, damage, or expense, direct or consequential, arising out of their use.