

Sunny Sol 150 - Jones Chemicals, Inc.
MSDS# 1201.9048 Revisions# 1994.01015

M A T E R I A L S A F E T Y D A T A S H E E T

Jones Chemicals, Inc.
80 Munson Street
LeRoy, New York 14482
(and Principal Cities)

For information, please contact the Jones Chemicals facility in your area at (603) 595-5688 or the Jones Chemicals Corporate Laboratory in Caledonia, New York at (716) 538-2311.

In the event of a transportation emergency,
Call CHEMREC: (800) 424-9300

SECTION I - IDENTIFICATION

TRADE NAME: Sunny Sol 150®
CHEMICAL NAME: Sodium Hypochlorite
FORMULA: NaOCl
DOT SHIPPING NAME: Hypochlorite Solution
DOT HAZARD CLASS: Corrosive Material
UN/NA NUMBER: UN 1791
DOT LABEL: Corrosive
DOT PLACARD: Corrosive
PACKING GROUP: III
REPORTABLE QUANTITY: Sodium Hypochlorite: 100 Pounds/45.4 Kilograms
CAS NUMBER: 7681-52-9

NFPA DESIGNATION: The NFPA has not rated sodium hypochlorite.

SECTION II - HAZARDOUS INGREDIENTS

MATERIAL	% BY WEIGHT	CAS NO.	OSHA PEL	ACGIH TLV
Sodium Hypochlorite	12.5-15.6	7681-52-9	Not Applicable	Not Applicable
Sodium Hydroxide	0.1-2.0	1310-73-2	2mg/m ³ ceiling	STEL/CEIL(c) 2mg/m ³ ceiling
Inert Ingredients	Balance	Not Applicable	Not Applicable	Not Applicable

CARCINOGENICITY STATUS: NTP - No, IARC - No, OSHA - No.

SECTION III - PHYSICAL DATA

APPEARANCE: Yellow-green liquid
BOILING POINT: 219°F (104°C) for 12.5% NaOCl by wt.
FREEZING POINT: - 11°F (- 24°C) for 12.5% NaOCl by wt.
ODOR: Chlorine
pH: 12.5 - 13.5 s.u. @ 25°C
VISCOSITY (Cs): 2.15 @ 23°C for 12.5% NaOCl by wt.
PERCENT VOLATILE BY VOLUME: Variable water plus products of decomposition
SOLUBILITY IN WATER: Complete
SPECIFIC GRAVITY (Water=1): 1.218 @ 20°C for 13.79 % NaOCl by wt.
VAPOR DENSITY (AIR=1): Not available
VAPOR PRESSURE (mm Hg): Variable water plus products of decomposition.

SECTION IV - FIRE AND EXPLOSION DATA

FLASH POINT (Test method): Not applicable
AUTO IGNITION TEMPERATURE: Not applicable
FLAMMABLE LIMITS IN AIR (Volume %): Not applicable
EXTINGUISHING MEDIA: Flood with water or carbon dioxide (CO₂)
SPECIAL FIRE FIGHTING PROCEDURES: Use National Institute of Occupational Safety & Health (NIOSH) approved respirator with acid type canister or use self-contained breathing apparatus.
Unusual fire and explosion hazards: material is a strong oxidizer. Contact with combustibles may initiate or promote combustion. Acid and heat accelerate decomposition. Decomposition products may include chlorine.

SECTION V - HEALTH HAZARD INFORMATION

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

No medical conditions are known to be aggravated by exposure.

ROUTES OF EXPOSURE

INHALATION: Fumes from spills can cause severe irritation and chemical burns to the nose, throat, and lungs. Very little hazard from properly stored solution.
SKIN CONTACT: Severe irritant, reddening of skin, can cause chemical burns to skin.
SKIN ABSORPTION: Same as skin contact.
EYE CONTACT: Severe irritant, corrosive, can severely burn eyes.
INGESTION: Causes irritation of membranes of the mouth, throat, and stomach pain and possible ulceration. LD50 (oral, rat) for 12.5% NaOCl is approximately 5 g/kg body weight.

EFFECTS OF OVEREXPOSURE

ACUTE OVEREXPOSURE

SWALLOWING: See "ingestion" under routes of exposure.
SKIN CONTACT: Irritant, reddening of skin, skin damage.
INHALATION: Fumes from spills are very irritating to mucous membranes.
EYE CONTACT: Extreme irritant, corrosive.

CHRONIC OVEREXPOSURE

EYE: Can cause damage.
SKIN: Can cause damage, chemical burns.

EMERGENCY AND FIRST AID PROCEDURES

IF CONTACT WITH EYES OCCURS: Flush with water for at least fifteen (15) minutes. Get medical attention.
IF CONTACT WITH SKIN OCCURS: Wash with plenty of soap and water.
INHALATION: Remove to fresh air. Call a physician if exposure is severe.
I. SWALLOWED: drink large amounts of water. Do NOT induce vomiting. Call a physician or poison control center immediately.

SECTION VI - REACTIVITY DATA

CONDITIONS CONTRIBUTING TO INSTABILITY

Solutions are fairly stable in concentrations below 10%. Stability decreases with concentration, heat, light, exposure, decrease in pH, and contamination with heavy metals, such as nickel, cobalt, copper, and iron.

INCOMPATIBILITY

Acids, alcohols, amines, ammonia, chlorinated isocyanurates, combustibles, cyanides, detergents, ethers, hydrocarbons, oxidizable materials, reducing agents. Corrosive to most metals.

DECOMPOSITION PRODUCTS

Hypochlorous Acid (HOCl), chlorine, hydrochloric acid. Composition depends upon temperature and decrease in pH. Additional decomposition products, which depend upon pH, temperature and time, are sodium chloride, sodium chlorate and oxygen.

CONDITIONS CONTRIBUTING TO HAZARDOUS POLYMERIZATION

Will not occur.

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED

Cleanup personnel must wear proper protective equipment (See Section VIII). Contain in diked area. Neutralize with sodium bisulfite or ferrous salt solutions. Place neutralized material in DOT specification approved container(s). Flush area with large amounts of water. Comply with all Federal, State and Local reporting requirements.

WASTE DISPOSAL

Contact Federal, State, County, and Local environmental regulators for guidance regarding proper disposal.

SECTION VIII - SPECIAL PROTECTION INFORMATION

VENTILATION REQUIREMENTS

Local exhaust is recommended.

SPECIFIC PERSONAL PROTECTIVE EQUIPMENT

RESPIRATORY: Use National Institute of Occupational Safety and Health (NIOSH) or Mine Safety and Health Administration (MSHA) approved respirator appropriate for this product when permissible exposure limits are exceeded.

EYES: Use chemical goggles and face shield.

GLOVES: Use chemical resistant rubber, plastic, or neoprene gloves.

OTHER: Use chemical resistant splash apron and boots. Safety shower and eye wash fountain should be located nearby.

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING

DANGER: This product is corrosive and may cause severe skin irritation or chemical burns to broken skin. Causes eye damage. Do not get in eyes, on skin or on clothing. Wear goggles and face shield and chemical resistant gloves when handling this product. Wash after handling. Avoid breathing vapors. Vacate poorly ventilated areas as soon as possible. Do not return until odors have dissipated.

PROPER STORAGE AND DISPOSAL REQUIREMENTS

Store this product in a cool, dry area away from direct sunlight and heat to avoid deterioration. In case of spill, flood areas with large quantities of water.

Disposal for domestic use: Do not reuse container. Rinse thoroughly before discarding in trash.

Disposal for all other uses: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or incineration, or, if allowed by state and local authorities, by burning. If burned, stay out of smoke.

Do not contaminate water, food, or feed by storage, disposal or cleaning of equipment.

STORE IN AN UPRIGHT POSITION**OTHER PRECAUTIONS**

STRONG OXIDIZING AGENT: Mix only with water according to label directions. Mixing this product with gross filth such as feces, urine, etc., or with ammonia, acids, detergents or other chemicals may release hazardous gases irritating to eyes, lungs and mucous membranes.

ADDITIONAL REGULATORY CONCERNS

EPA: May not be used for disinfection or sanitization without prior approval by EPA. Repackagers must obtain EPA registration and establishment numbers.

FIFRA: This product is regulated under the Federal Insecticide, Fungicide, and Rodenticide Act (FIFRA) if used as a disinfectant or sanitizer.

TSCA: Included in the Toxic Substances Control Act (TSCA) Inventory of Chemical Substances.

MSDS PREPARED BY: Jones Chemicals, Inc.
80 Munson Street
LeRoy, New York 14423
Corporate Environmental Department 716-768-6281
Corporate Laboratory 716-538-2311

ISSUE DATE: 12/05/94
SUPERSEDES ISSUE DATED: 03/20/90

The information herein is given in good faith but no warranty, expressed or implied is made.